

# RH4

BUILT- IN SIDE DOOR BATHING SYSTEM



The RH4 is a side door bathing system that allows full immersion bathing from a seated position. The RH4's unique design allows for easy wheelchair transfers and is compatible with most patient transfer devices. The contoured interior enables the bather to sit in a slightly reclined position. Tub Size is 60" x 30".



rane®

# Technical Specifications

Product specifications and operational procedures are subject to change by manufacturer without prior notification

## STANDARD UNIT: MODEL# RH4

**Description:** Model RH4 is a built-in, 60-gallon, side access bathing tub.

**Construction:** The tub shell is a seamless piece of 3/16" thick fiberglass-reinforced polyester laminate. Critical areas are reinforced with a 1/4" thick core of end-grain balsa and additional layers of fortifying laminate. The sanitary gelcoat is an ISO/NPG type-finish.

**Side Access Door:** The locking door can be left or right hinged, and has a compression-type seal that is Teflon impregnated.

**Lift Access Opening:** The front opening allows access to drain and provides clearance for most mobile floor lifts.

**Drain and Overflow Assembly:** An ample 1.5" drain is installed with an overflow.

**Grab Bars:** Two 7.5" aluminum grab bars are firmly mounted to the interior walls of the tub.

**Leveling Legs:** The sturdy stainless steel leveling legs will adjust up to 2" per leg.

**Air Spa Option:** The air spa system features a control system that allows for increasing the air flow at a gradual rate of speed at the push of a button. A ceramic heating element provides warm air that maintains the water temperature and warms the surface of the tub. Backflow prevention spring loaded jets eliminate the need for back flushing air lines, providing for longer life than rubber flap style jets.

**Whirlpool Option:** The whirlpool option is a 2-jet one-horsepower WOW pump system with pneumatic actuator switch.

## PERFORMANCE DATA:

**Tub Capacity:** 60 gallons

**Occupied Tub Capacity (approx):** 48 gallons

**Drain Flow Rate:** 1.5" drain – 1.92 minutes

## SERVICE CONNECTIONS:

**Drain:** 1.5" standard

**Electrical for WP or Air Blower:** 115V AC, 60Hz, 15A service with a GFI Circuit (not supplied by Rane)

## MANUFACTURING AND TESTING:

This unit is manufactured in Sparta, Tennessee, USA. Each unit passes a thorough quality control review and is tested for proper operation prior to shipping.

## WARRANTY:

Standard 1 year limited warranty

